

Product Fiche (EN-GB)



Supplier Name	Titon			
Supplier Address	894 The Crescent Colchester Business Park Colchester Essex CO4 9YQ			
Model	HRV1.35 Q+ Eco HMB C (Enthalpy) **CHECK FW No WITH DEVELOPS*			
Model Identifier	TP408HMBE			
Specific Energy Consumption Class	SEC Class B (Average Climate) SEC Class A+ (Cold Climate) SEC Class E (Warm Climate)			
Declared Typology	BiDirectional			
Type Of Drive Installed	Variable Speed Drive			
Type Of Heat Recovery System	Recuperative			
Thermal efficiency of heat recovery	70%			
Maximum flow rate	237m ³ /h			
Effective Power Input	61.50W			
Sound Power Level	49dB			
Reference Flow Rate	0.0461m ³ /s			
Reference Pressure Difference	50Pa			
SPI	0.3709W/(m ³ /h)			
Ventilation Control Factor	0.85 *			
Declared Maximum Internal Leakage Rate	5%			
Declared Maximum External Leakage Rate	5%			
		Cold Climate	Average Climate	Warm Climate
SEC	kWh/(m².a)	-65.8	-32.0	-10.1
AEC Annual Electricity Consumption	kWh/a	9.2	3.8	3.4
AHS Annual Heating Saved	kWh	80.0	40.9	18.5
Visual Filter Warning Position	Timestrip or optional remote mounted Auralite display Filter change information contained in the user manual			
Pre/dis-assembly instructions	www.titon.com			

* Using the internal humidity sensor to provide central demand control