

110x54mm - Rectangular Ducting

plus Accessories and Terminals

110x54mm PVC	Product Code	Free Area = 5,424mm ²	Static Pressure Drop (in Pa)		
		Components	8l/s	15l/s	30l/s
	8960109	Rectangular Duct - 1.0m Long	0.6	2.2	8.6
	8960096	Rectangular Duct - 1.5m Long	0.9	3.3	12.8
	ENQ	Rectangular Duct - 2m Long	1.2	4.4	17.1
	8960094	90° Bend - Horizontal	2.8	9.8	39.8
	8960081	45° Bend - Horizontal	1.1	3.7	15.5
	8960095	90° Bend - Vertical	4.4	15.6	62.8
	8960003	45° Bend - Vertical	0.7	2.6	12.7
	8960082	Tee Piece	n/a		
	8960091	Duct Connector	0.1	0.3	1.4
	8960131	Flexible Duct Connector	0.1	0.3	1.4
	8960084	Fixing Bracket	n/a		
	8960108	110x54mm to 204x60mm Horizontal Adaptor	n/a		
	8960111	110x54mm to Ø100mm Horizontal Adaptor	1.1	3.7	14.6
	8960080	110x54mm to Ø100mm Horizontal Short Adaptor - Male	1.4	4.8	20.4
	8960093	110x54mm to Ø100mm Vertical Adaptor - Male	2.3	8.1	33.1
	8960092	110x54mm to Ø100mm Vertical Adaptor - Female	2.3	8.1	33.1
	Product Code	Terminals	8l/s	15l/s	30l/s
	8960089	External Louvred Grille (Free Area; 2,600mm ²) - Brown 	4.3	15.0	48.1
	8960090	External Louvred Grille (Free Area; 2,600mm ²) - Terracotta 			
	8960088	External Cowled Grille (Free Area; 5,800mm ²) - White 	2.4	8.4	30.4
	8960085	External Cowled Grille (Free Area; 5,800mm ²) - Brown 			
	8960086	External Cowled Grille (Free Area; 5,800mm ²) - Beige 			
	8960087	External Cowled Grille (Free Area; 5,800mm ²) - Terracotta 			
	Product Code	Flexible PVC Duct	8l/s	15l/s	30l/s
	8960074	Rectangular – 1m length	n/a		
	8960076	Rectangular – 3m length	n/a		
	Product Code	Fire Protection	8l/s	15l/s	30l/s
	QRS110/54	110x54mm Fire Sleeve (Fire Rating 120 mins)	n/a		
	QRS110/54SS	110x54mm Fire Slim Sleeve (Fire Rating 120 mins)	n/a		
	FW110X54X100	Intumescent Wrap (Fire Rating 120 mins) to work with	n/a		
	FWS110X54X141	Metal Retaining Sleeve - for partition walls up to 132mm	n/a		