

Access Panel - Fire Rated

HRV/CME Accessories - Metal 1hr fire rated access panel

For use in a wide range of dwellings

Titon's picture frame access panels offer multi performance, with 1 hour fire rated steel access panels that feature mineral wool and draught stripping, allowing for greatly reduced air leakage and an excellent acoustic performance.

Titon's Fire Rated Access Panels provide excellent access to our CME units that will be located in a ceiling void. They allow suitable access for applications where a 1 hour fire rating is required.

Accessory



Features & Benefits

- Purpose made product saves time and money compared with traditional joiner-made access doors
- Fire rating independently tested by Exova Warrington fire
- Mineral wool insulation and draught stripped to reduce the opportunity of air leakage in application
- 32mm low profile frame ideal for installation with 15mm plaster board
- Flush fitting door panels with excellent aesthetic appearance and finish
- Visible picture frame surround smartly conceals cut out edges and contributes to a faster installation
- Enduring polyester powder coated finish
- Allows for painting if required
- Quick and straightforward to install
- Universal door handing
- Hinged door panel with T-key lock mechanism - Key lock available upon request
- Quick release door panel mechanism fully removes to the door for maximum access
- Acoustic performance of 33dB

Material and colour choice

- Electro galvanised mild steel
- Glass wool insulation (45kg/m³)
- Polyester powder coated smooth finish 20% Gloss
- White – RAL 9016

Installation advice

- Please contact the Titon's Technical team

Care and maintenance

- Clean using a soft cloth with a mild detergent
- Spare keys available upon request
- Lock and hinge mechanism can be oiled with a standard metal lubricant if required

Product Number	Frame Fitting	Clear Opening	Overall Panel and Frame Dimension	Door and lock type
89802	605 x 605mm	560 x 560mm	650 x 650mm	Hinged with T-key lock

