aura-t[™] SMART (WiFi)

HRV Q Plus Touch Screen WiFi Programmer panels

For use with Titon HRV Q Plus B Model Range

aura-t" SMART (WiFi) is a simple yet striking touchscreen controller for programming, commissioning and occupancy control for Titon's range of Mechanical Ventilation Heat Recovery (MVHR) units.

The aura-t[®] SMART (WiFi) controller allows straightforward operation of ventilation speeds. Offering WiFi connection via Titon's auraSMART[®] app available via Android or iOS mobile devices.

Product Number

aura-t[™] SMART (WiFi) - TP736



Description

Titon's aura-t" SMART (WiFi) is for commissioning and monitoring a Titon TP***B HRV Q Plus unit.

aura-t[™] SMART (WiFi) provides the following functions:

- Compatible with auraSMART[®] app
- WiFi connection
- Digital 4 speed switch
- Auto timed speed mode
- 7-day, 4 events per day programmable Speed 1 timer
- Filter change indicator
- Internal MVHR humidity set point adjustment
- Boost inhibit functions linked to timed Speed 1 (avoiding night time boosting via either switch inputs or humidity)

aura-t[™] SMART (WiFi) is an icon based rather than language specific controller.


Features & Benefits

- Simple user friendly interface
- WiFi connection
- Compatible with auraSMART* app
- Compact sleek design
- 4 speed manual control (OFF feature)
- 7 day programmable automatic Speed 1 timer
- Real-time fan commissioning for all speeds
- Filter change alert indicator
- Internal humidity threshold adjustment
- Kitchen & wet room boost overrun time adjustment
- Programmable boost inhibit
- Switch configuration menu
- Time and day display
- Backlight with automatic dimming
- Real-time indication of HRV status and operating mode
- Optional passcode protected commissioning and setup screens
- Summer bypass configuration menu
- 8 hour time out for manual operation
- Fan failure indication
- Fan speed cloning copy settings from one to another
- Compatible from software version FW0027-0206 onwards circa. June 2016

Specification

Dimensions	87mm wide x 87mm high x 24mm deep supplied with 3 metre connection cable.
Weight:	185g
Finish:	High gloss finish
Materials:	ABS
Guarantee period: 1 year	
Electrical:	12V DC

Drawing and Dimensions



Dimensions in mm