

Product Fiche en-GB



Supplier Name	Titon			
Supplier Address	894 The Crescent Colchester Business Park Colchester Essex CO4 9YQ			
Model	HRV4 Q Plus Eco			
Model Identifier	TP431B2F/LR-T			
Specific Energy Consumption Class	Cold Climate	Average Climate	Warm Climate	
	SEC Class A+	SEC Class A+	SEC Class E	
Declared Typology	BiDirectional			
Type Of Drive Installed	Variable Speed Drive			
Type Of Heat Recovery System	Recuperative			
Thermal efficiency of heat recovery	85%			
Maximum flow rate	443.00m ³ /h			
Effective Power Input	73.10W			
Sound Power Level	49.00dB			
Reference Flow Rate	0.09m ³ /s			
Reference Pressure Difference	50.00Pa			
SPI	0.24W/(m ³ /h)			
Ventilation Control Factor	0.65			
Declared Maximum Internal Leakage Rate	5.00%			
Declared Maximum External Leakage Rate	5.00%			
		Cold Climate	Average Climate	Warm Climate
SEC	W/(m³/h)	-80.80	-42.30	-17.60
AEC Annual Electricity Consumption	W/(m³/h)	7.10	1.70	1.20
AHS Annual Heating Saved	W/(m³/h)	89.70	45.90	20.70
Visual Filter Warning Position	Timestrip or optional remote mounted Aurastat/Auramode display Filter change information contained in the user manual			
Pre/dis-assembly instructions	None			

* Using 0-10V room sensors to provide local demand control